

# 123/1234 Hinge Options

Application	Hinge Cap	Optional Accuride 1234 Hardware Kit	Mfg. Part Number	Door Thickness		Maximum Tab		Minimum Gap		Door Clearance		
				mm	inches	mm	inches	mm	inches	mm	inches	
Inset	35 mm	4180-0391-XE	<b>Salice</b> 4180-0390-XE Supplied with 123, Self Close C2P7G33 3 mm Base BAR3R39	19.0	3/4	8.0	5/16	0.7	1/32	1.0	1/32	
				20.6	13/16	9.5**	3/8**			0.9		
				** Requires hinge adjustment to achieve door gap. May require notching.								
		N/A	<b>Mepla</b> 146-305-53-0015 Base 314-393-81-0015	19.0	3/4	6.0	1/4	0.7	1/32	2.0	5/64	
				20.6	13/16					0.4	1/64	
			<b>Blum</b> Self Close 71T9650 Free Swing 70T9650 0 mm Base 175H9100	19.0	3/4	8.0	5/16	2.2	3/32	5.5	7/32	
				20.6	13/16					3.9	9/32	
				22.2	7/8					2.3	3/32	
				23.8	15/16					0.7	1/32	
Inset for Thick Doors	40 mm	4180-0313-XE	<b>Salice</b> Self Close CFA7P99 Free Swing CFA5P99 0 mm Base BAR3R09	19.0	3/4	14.0	9/16	0.7	1/32	13.0	1/2	
				20.6	13/16					11.4	7/16	
				22.2	7/8					9.8	3/8	
				23.8	15/16					8.2	5/16	
				25.4	1					6.6	1/4	
				27.0	1-1/16					5.0	3/16	
				28.6	1-1/8					3.4	1/8	
				30.2	1-3/16					1.6	1/16	
				31.8	1-1/4					0.0	0	
		N/A	<b>Mepla</b> 146-425-53-0015 Base 314-393-81-0015	19.0	3/4	6.0	1/4	0.7	1/32	5.5	7/32	
				20.6	13/16					3.9	5/32	
				22.2	7/8					2.3	3/32	
				23.8	15/16					0.7	1/32	
			25.4 1 * 27.0 1-1/16* 28.6 1-1/8* 30.2 1-3/16*	9.0	3/8	1.7	1/16	2.1	5/64			
								0.5	1/64			
								1.9	5/64			
								0.3	1/64			
*Spacers required for doors 1 inch thick and over.												
									Overlay Amount			
Overlay	40 mm	4180-0314-XE	<b>Salice</b> Self Close CFA7G99 Free Swing CFA5G99 0 mm Base BAR3R09	19.0	3/4	15.0	19/32	11.3	7/16	2.0	5/64	
				20.6	13/16					0.4	1/64	
		N/A	<b>Mepla</b> 146-425-53-0015	19.0	3/4	11.0	7/16	5.0	3/16	5.5	7/32	
				20.6	13/16					3.9	5/32	
				22.2	7/8					2.3	3/32	
23.8	15/16	0.7	1/32									

**Caution:** For doors under 36" tall, hinge carrier strip needs to be modified. Hinge carrier strip required for all doors.