

# 1332/1432 Hinge Options

Application	Hinge Cap	Optional Accuride Hardware Kit	Mfg. Part Number	Door Thickness		Maximum Tab		Minimum Gap		Door Clearance			
				mm	inches	mm	inches	mm	inches	mm	inches		
Inset	35 mm	4180-0389-XE Zinc Finish  4180-0407-XE Black Finish	<b>Salice</b> Supplied with 1332 Self Close C2P7A33 Zinc Free Swing C2P5A99 Base BAR3R39	19.0	3/4	8.0	5/16	2.3 ■◆	3/32 ■◆	1.4	1/16		
				20.6	13/16	9.0 ■	11/32 ■	1.8 ●	1/16 ●	0.3	1/64		
		* Requires hinge lateral adjustment to achieve door gap    * May require notching    ◆ For smaller gap, increase tab											
		N/A	<b>Blum</b> Self Close 71T9550 Free Swing 70T9550 Base 175H9100	19.0	3/4	8.0	5/16	3.3 ■◆	1/8 ■◆	5.4	7/35		
				20.6	13/16					3.8	5/32		
			■ May require notching.    ◆ For smaller door gap, increase tab.										
		<b>Mepla</b> 146-305-53-0015 Base 314-393-81-0015	19.0	3/4	6.5	1/4	1.8 ●	1/16 ●	2.4	3/32			
			20.6	13/16					8.0	1/32			
		Inset for Thick Doors	40 mm	4180-0394-XE	<b>Salice</b> Zinc Self Close CFA7G99 Zinc Free Swing CFA5G99 Base 3 mm BAR3R39	19.0	3/4	15.0	19/32	2.3	3/32	14.4	9/16
						20.6	13/16					12.8	1/2
22.2	7/8					11.2	7/16						
23.8	15/16					9.6	3/8						
25.4	1					8.0	5/16						
27.0	1-1/16					6.4	1/4						
28.6	1-1/8					4.8	3/16						
30.2	1-3/16					3.2	1/8						
31.8	1-1/4					1.6	1/16						
N/A	<b>Mepla</b> 146-425-53-0015 314-393-81-0015			19.0	3/4	8.0	5/16	1.3	1/16	7.0	9/32		
				20.6	13/16					5.4	7/32		
				22.2	7/8					3.8	5/32		
				23.8	15/16					2.2	3/32		
				25.4	1					6.0	1/32		
				27.0 ◆	1-1/16 ◆					2.0	3/32		
				28.6 ◆	1-1/8 ◆					4.0	1/32		
				30.2 ○◆	1-3/16 ○◆					11.0	7/16		
				31.8 ○◆	1-1/4 ○◆					14.0	9/16 ○		
○ Requires 3 mm (1/8") notch to the back of the door.    ◆ Requires 1 spacer, 3 mm (1/8")    ◆ Requires 2 spacers, 6 mm (1/4")													
								<b>Overlay Amount</b>					
Overlay	40 mm	4180-0292-XE	<b>Salice</b> Zinc Self Close CFA7A99 Zinc Free Swing CFA5A99 Base BAR3R09	19.0	3/4	15.0	19/32	11.7	7/16	0.4	1/64		

**For Additional Hinges** - add 1 more spacer to secondary hinges.

**Note:** On thicker doors, mortise hinge cup into door back to improve door-to-slide clearance.

**CAUTION:** For doors under 36" tall, hinge carrier strip needs to be modified. Hinge carrier strip required for all doors.