

Product details

MINIPRESS P - Boring and insertion machine, vertical, 240 V / 60Hz, extraction system connection 100 mm, Market-specific Canada, Market-specific USA



Part number	M53.2053US
Item number	04000958
Color / finish	Orange
Packaging quantity	1
Weight per 1,000 Pcs in kg	54,657.941
EAN code	9009494975208
UPC code	

Technical attributes

Attribute	Value
type of machine	MINIPRESS P
type of device	table device
additions	Market-specific Canada
additions	Market-specific USA
control and drive	electro-pneumatic
boring and processing direction	vertical
processing possibility	boring and component insertion
boring head assembly	through quick exchange
type of connection	1PH/PE
nominal voltage	240 V
nominal current	7 A
motor performance	1,1 kW
frequency	60 Hz
safety certificate	CSA compliant version
length of base ruler	600 mm
dimension breakdown	Calibration from zero position: 11 13/16 inch left, 11 13/16 inch right
dimension breakdown	Calibration from zero position: 300 mm left, 300 mm right
connection pressure	5 bar to 7 bar
air consumption / cycle	1.5 liters per cycle
maximum wood thickness	45mm (boring only)
X-coordinate (parallel ruler)	300mm to left(MINUS),0mm(CENTER POINT),300mm to right(PLUS)
Y-coordinate (right angle against ruler)	Vertical, from 0 to 70mm backwards
Z-coordinate (height)	45 mm downwards (MINUS)
processing of	955.TIP-ON and 970.BLUMOTION adapter plates (wing plate and horiz.)
processing of	AVENTOS front fixing bracket
processing of	AVENTOS lift mechanism
processing of	front fixings
processing of	Cabinet profiles
processing of	RTA fitting
processing of	LEGRABOX
processing of	System boring

Product details

Attribute	Value
processing of	MERIVOBX
processing of	mounting plates
processing of	MOVENTO
processing of	Hinges
processing of	SERVO-DRIVE switch
processing of	TANDEM
processing of	TANDEMBOX
processing of	SERVO-DRIVE bracket profile attachment or attachment bracket
boring for	Front fixings
boring for	Cabinet profiles
boring for	System boring
boring for	Hinges
boring for	Mounting plates
net weight of assembly device	47 kg
dimensions(height/width/depth)	710 mm, 610 mm, 760 mm
Connection to pneumatics	Tube
Pneumatic connection size	LW 10
Diameter of extraction socket	100 mm
Plug	NEMA 6-15P